PRECISION FABRICS GROUP

Code: 60002 | Style: 56030

Polyester Peel | Release Ply

Code 60002 is similiar to 60001 except it contains black identification stripes for easy visibility. Code 60002 is designed for vacuum bag lay-up composites and metal-to-metal bonding structures. Code 60002, 100% polyester fiber melts at approximately 480°F (249° C) and is resistant to phenolic resin system degradation. The fabric leaves a medium surface impression for priming and secondary bonding. It is available in precision slit widths of 58 inches or less.

Code 60002 Peel Ply is available in:

FIN 060 - NAT Scoured and Heat-Set finish Identification Printing Available

Code 60002 Release Ply is available in:

FIN 061 - SRB

Super Release Blue An inert, heat-stabilized, cross-linked polymer finish

	US	Metric	
WIDTH	60 in	152 cm	nominal
WEIGHT	2.70 oz/yd²	92 g/m²	nominal
WARP COUNT	72 ends/in	28 ends/cm	nominal
FILL COUNT	57 picks/in	22 picks/cm	nominal
THICKNESS	5.0 mils	0.13 mm	nominal
MD GRAB TENSILE	190 lbs	846 Newtons	nominal
XD GRAB TENSILE	150 lbs	668 Newtons	nominal
EXTRACTIONS (Petroleum Ether)	0.5%		(max)
ROLL LENGTHS	300 yd	274 m	nominal

The information is not to be construed as a specification or a license to operate under, nor is it intended to suggest infringement of any existing patents. We believe the information in the bulletin is correct. No warranty of accuracy is implied.

PrecisionFabricsGroup

engineered materials & technical fabrics