

## RELEASE FABRICS

<b>A-8888</b>	Nylon peel ply fabric with an inert, heat stabilized, fully cross-linked, polymer finish Weight: 2.2 oz./yd <sup>2</sup>
<b>B-4444</b>	Nylon peel ply fabric with an inert, heat stabilized, fully cross-linked, polymer finish Weight: 1.70 oz./yd <sup>2</sup>
<b>E-5555</b>	Fiberglass fabric with an inert, heat stabilized, fully cross-linked, polymer finish Weight: 3.11 oz./yd <sup>2</sup>
<b>T-3333</b>	Fiberglass fabric with a fluorocarbon release agent Weight: 8.4 oz./yd <sup>2</sup>
<b>200 TFP</b>	Porous TFE coated fiberglass fabric Weight: 1.8 oz./yd <sup>2</sup>
<b>200 TFNP</b>	Non-porous TFE coated fiberglass fabric Weight: 3.2 oz./yd <sup>2</sup>
<b>200 TFP-1</b>	Porous TFE coated fiberglass fabric, in .001" thick only Weight: 1.36 oz./yd <sup>2</sup>
<b>1581-C</b>	Fiberglass fabric with an inert, heat stabilized, fully cross-linked, polymer finish Weight: 9.0 Oz./yd <sup>2</sup>

**NOTE:** Release Fabrics are available in narrow roll widths by Hot Knife Slitting (eliminates edge fraying), except T 3333, E 5555 & 1581-C.

Please call **801-265-0111** for Data Sheets or other information.

Note: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No warranties of any kind are made except that materials supplied are TMI standard quality. All risk and liability arising from handling, storage and use of TMI products, as well as compliance with applicable legal restriction, rest with the buyer.