

TMR-6200

High Performance ETFE Release Film

Features:

- High temperature, fluoropolymer release film, offers excellent toughness and high elongation.
- Compatible with most commonly used resin systems.
- Suitable for cure cycles up to 450°F (232°C)
- Red and blue translucent colors are easily visible against cured parts
- Color will not transfer to composite.

Properties:

Technical Data:	Test Method:	Typical Value:
Maximum use temperature		450°F (232°C)
Continuous use temperature	UL-746 B	350°F (177°C)
Color		Red, Blue
Tensile Strength	ASTM D-882	7,000 psi
Elongation (at break)	ASTM D-882	300 %
Yield		100ft ^{2/} lb/mil

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

Availability:

Standard roll sizes: 60" x .001" x 417"

50" x .001" x 500'

- Alternative sizes available upon request (minimum order quantities may apply.)
- Perforation: Please call for availability.

Storage:

Store in original packaging and protect from the environment.

Health & Safety:

• Handling of these products must conform to individual company guidelines and health and safety regulations.

Technology Marketing, Inc.

P: 801.265.0111 • F: 801.265.0184 6122 Stratler Street • Salt Lake City, UT 84107 USA • customerservice@tmi-slc.com • www.tmi-slc.com

ISO 9001:2015 & AS9120B Certified

Note: Data provided is for information only and does not constitute any warranty for the product as the conditions and varying methods of use are beyond our control, Technology Marketing Inc. shall not be liable for any special indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use or inability to use these materials. These materials are provided "as is" without warranty of any kind, either expressed or implied including, but not limited to the implied warranties of merchantability or fitness for a particular purpose

Form Rev.A Rev. 03/24/2020